

V-STRUM 1050 / XT



*Image shown with optional accessories.

V-STRUM 1050/XT

Release your inhibitions and go out in the wild.
The adventurous spirit of the new generation
V-STRUM 1050/XT with its intelligent functionality
gives you limitless potential.
Go beyond your boundaries and dive into
your next adventure with the V-STRUM 1050/XT.

EXPAND YOUR HORIZON.



Bell Village 405 1000
Flacq 405 1088
Forbach 405 1100
Rodrigues 831 0592

V-STRUM 1050XT



Champion Yellow No.2 (YU1)



Pearl Brilliant White / Glass Blaze Orange (B1F)



Glass Sparkle Black (YVB)

V-STRUM 1050



Glass Sparkle Black (YVB)



Glass Sparkle Black / Pearl Brilliant White (B1G)



Glass Sparkle Black / Solid Iron Gray (BTH)

SPECIFICATIONS

Overall length	2,265 mm (89.2in)	
Overall width	V-STRUM 1050XT	: 940 mm (37.0 in)
	V-STRUM 1050	: 870 mm (34.3 in)
Overall height	V-STRUM 1050XT	: 1,465 mm (57.7 in)
	V-STRUM 1050	: 1,515 mm (59.6 in)
Wheelbase	1,555 mm (61.2 in)	
Ground clearance	V-STRUM 1050XT	: 160 mm (6.3 in)
	V-STRUM 1050	: 165 mm (6.5 in)
Seat height	V-STRUM 1050XT	: 850 mm (33.5 in)
	V-STRUM 1050	: 855 mm (33.7 in)
Curb mass	V-STRUM 1050XT	: 247 kg (544.6 lbs)
	V-STRUM 1050	: 236 kg (520.4 lbs)
Engine type	4-stroke, liquid-cooled, DOHC, 90° V-twin	
Bore x stroke	100.0 mm x 66.0 mm (3.937 in x 2.598 in)	
Engine displacement	1,037 cm ³ (63.3 cu in)	
Compression ratio	11.5 : 1	
Fuel system	Fuel injection	
Starter system	Electric	
Lubrication system	Wet sump	
Transmission	6-speed constant mesh	
Primary reduction ratio	1.838 (57/31)	
Final reduction ratio	2.411 (41/17)	
Suspension	Front	Inverted telescopic, coil spring, oil damped
	Rear	Link type, coil spring, oil damped
Rake / trail	25°30' / 109 mm (4.29 in)	
Brakes	Front	Disc, twin
	Rear	Disc
Tyres	Front	110/80R19M/C 59V
	Rear	150/70R17M/C 69V
Ignition system	Electronic ignition	
Fuel tank capacity	20.0 L (5.3 US gal / 4.4 Imp gal)	
Oil capacity (overhaul)	3.5 L (3.7 US qt / 3.1 Imp qt)	