



SUZUKI

THE NEW

DR-Z
4SM

**ATTACK THE
TRACK**



Tel: 405 1000 | Email: emcarmoto@emcar.mu | Web: www.emcar.mu




Your streets. Your playground.

Dominate the streets. Take command of supermoto tracks. Or simply put the pleasure back into your daily commute. The new DR-Z4SM provides a level of faithful performance and freedom that will boost your confidence and free you to ride unfettered. So, get out there. The streets are your playground to enjoy.




○ **Colour: Solid Special White No. 2 (30H)**



Tough steel frame



398cm³ Four-stroke Liquid-cooled DOHC Engine



Suzuki Intelligent Ride System

KEY FEATURES

- The DR-Z4SM adopts a new frame designed to respond faithfully to your will. Formed from steel pipe, the frame is rigid, strong and supple enough to handle rough surfaces, and it absorbs shocks well to reduce rider fatigue.
- Already famed for its performance and reliability, the compact 398cm³ liquid-cooled DOHC dry-sump engine has been thoroughly updated to enhance its torquey, free-revving nature to deliver a superior balance of performance and controllability, and to comply with the latest emission and noise regulations.
- The Suzuki Intelligent Ride System (S.I.R.S.) features a robust collection of advanced electronic rider assist functions. These include Suzuki Drive Mode Selector (SDMS), the Suzuki Traction Control System (STCS) with G (Gravel) mode, a setting that helps the rider maximize off-road performance, the Ride-by-wire Electronic Throttle System, ABS with Rear ABS OFF mode, and the Suzuki Easy Start System.
- The chassis geometry and riding position were developed with an emphasis on stability and control. This realizes a riding posture that is more conducive to higher speed runs on the streets or on supermoto tracks. Not only does this posture help you maneuver the DR-Z4SM with greater ease, it also contributes to greater stability and comfort that is less tiring on long rides.
- Both the high and low beams are incorporated into one bright LED projector headlight that is compact, light and durable. LED position lights integrated right into the turn signal assemblies help round out the functional yet minimalistic lighting scheme

Specifications

Overall Length	2,195mm (86.4 in)
Overall Width	885mm (34.8 in)
Overall Height	1,190mm (46.9mm)
Wheelbase	1,465mm (57.7 in)
Ground clearance	260mm (10.2 in)
Seat height	890mm (35.0 in)
Curb weight	154kg (340 lbs)
Engine type	4-stroke, single-cylinder, liquid-cooled, DOHC
Bore x stroke	90.0 mm x 62.6 mm (3.5 in. x 2.5 in.)
Engine displacement	398 cm (24.3 cu. in.)
Compression Ratio	11.1:1
Fuel system	Fuel injection
Starter system	Electric
Lubrication system	Dry sump
Transmission	5-speed constant mesh
Front suspension	Inverted telescopic, coil spring, oil damped
Rear suspension	Link type, coil spring, oil damped
Rake / trail	26.5°/95mm (3.74 in)
Front brakes	Disc
Rear brake	Disc
Front tire size	120/70R17M/C 58H, tube type
Rear tire size	140/70R17M/C 66H, tube type
Ignition system	Electronic ignition
Fuel tank capacity	8.7 L (2.3/1.9 US/Imp gal)
Oil capacity(overhaul)	1.9 L (2.0/1.7 US/Imp qt)
Fuel consumption	29.4 km/L (3.4 L/ 100 km) in WMTc
CO ₂ emissions	80 g/km in WMTc



Bell Village 405 1000
Flacq 405 1088
Forbach 405 1110
Rodrigues 831 0592